



NOTES:
 1. ALL SEWING SEPTIC COMPONENTS SHALL BE PLACED CLEAN, CRUSHED, AND FILL WITH CLEAN SAND (PER TYP. 2, (FOOT NOTS FROM SD))

The contractor shall verify the location and depth of all existing utilities before excavation. The contractor shall be responsible for obtaining all necessary permits and shall obtain a copy of the site plan from the Town of Dover. The contractor shall be responsible for obtaining all necessary permits and shall obtain a copy of the site plan from the Town of Dover. The contractor shall be responsible for obtaining all necessary permits and shall obtain a copy of the site plan from the Town of Dover.

GRAPHIC SCALE
 1 inch = 20 feet

<p>APPLICANT/TOWN OF DOVER</p> <p>GLM Engineering 19 EXCHANGE STREET HOLLISTON, MA 01745 P: 508-423-1100 F: 508-423-1101 WWW.GLMENGINEERING.COM</p>	<p>BENCH MARK 5946 SFT N. 30° W. 1/4" M. 6.51-102.97 (DATA - ASSUMED) CORNER CORN. P. 46.121-102.97</p>
<p>PROPOSED SEWAGE DISPOSAL SYSTEM #46 SPRINGDALE AVE. DOVER, MASSACHUSETTS</p>	<p>DESIGN SCALE: 1" = 20' JOB #1526-SEP SHEET #2 OF 2</p>